

Super-Temp

Wire & Cable, Inc.

Manufacturer of High Temperature Wire and Cable

TYPE ET M16878/6 NEMA HP3 ETX

UL1371 TAGGED

Conductor: Solid or Stranded Silver Plated Copper

Extruded PTFE Insulation

Characteristics:

Temperature Rating: MIL-W-16878/NEMA HP3: 200C UL: 105C

Voltage Rating: MIL-W-16878/NEMA HP3: 300V UL: NO VOLTAGE

MIL SPEC DESIGNATION	DESCRIPTION	AWG	STRANDING	COND DIAMETER	MIN	MAX	NOM LBS/1000'
					DIAMETER		
M16878/6-BAA	XET 32 1/32	32	1/32	0.008	0.016	0.022	0.44
M16878/6-BAB	XET 32 7/40	32	7/40	0.009	0.020	0.024	0.50
M16878/6-BBA	XET 30 1/30	30	1/30	0.010	0.020	0.024	0.62
M16878/6-BBB	XET 30 7/38	30	7/38	0.012	0.022	0.026	0.70
M16878/6-BBE	XET 30 19/42	30	19/42	0.012	0.022	0.026	0.75
M16878/6-BCA	XET 28 1/28	28	1/28	0.013	0.023	0.027	0.83
M16878/6-BCB	XET 28 7/36	28	7/36	0.015	0.025	0.029	0.96
M16878/6-BCE	XET 28 19/40	28	19/40	0.015	0.025	0.029	1.01
M16878/6-BDA	XET 26 1/26	26	1/26	0.016	0.026	0.030	1.16
M16878/6-BDB	XET 26 7/34	26	7/34	0.019	0.029	0.033	1.31
M16878/6-BDE	XET 26 19/38	26	19/38	0.019	0.029	0.034	1.36
M16878/6-BEA	XET 24 1/24	24	1/24	0.020	0.030	0.034	1.68
M16878/6-BEB	XET 24 7/32	24	7/32	0.024	0.034	0.038	1.93
M16878/6-BEE	XET 24 19/36	24	19/36	0.024	0.034	0.039	1.97
M16878/6-BFA	XET 22 1/22	22	1/22	0.025	0.035	0.040	2.55
M16878/6-BFB	XET 22 7/30	22	7/30	0.030	0.040	0.044	2.89
M16878/6-BFE	XET 22 19/34	22	19/34	0.030	0.040	0.046	2.97
M16878/6-BGA	XET 20 1/20	20	1/20	0.032	0.042	0.046	3.78
M16878/6-BGB	XET 20 7/28	20	7/28	0.038	0.048	0.052	4.25
M16878/6-BGE	XET 20 19/32	20	19/32	0.038	0.048	0.052	4.44